

Axle Spacing Report for Canadian Weights

Commercial Vehicle Services PO Box 47367 7345 Linderson Way SW Olympia, WA 98504-7367 360-704-3640 / Fax 360-704-6391 www.wsdot.wa.gov/commercialvehicle

Name of Owner	Contact Name			
Address	City	State	Zip	
Phone (Include Area Code)	Fax (Include Area Code)			

Description of Equipment (This section must be filled out completely)

Unit No.

	Telephone (The education must be miss sat sempletely)				G	
	# Tires	Size	Steer Axle	Drop Axle	Axle Spacings	
Axle 1						
Axle 2				1-2	Ft.	ln.
Axle 3				2-3	Ft.	ln.
Axle 4				3-4	Ft.	ln.
Axle 5				4-5	Ft.	ln.
Axle 6				5-6	Ft.	ln.
Axle 7				6-7	Ft.	ln.
Axle 8				7-8	Ft.	ln.

- (A) Primary steering axle 600 lbs. (272 kg) per inch (25.4 mm) of width of tire. *With a maximum limit of 12,100 lbs.
- (B) Other axles 500 lbs. (227 kg) per inch of width of tire.*.
- (C) Single axles 20,000 lbs. (9,100 kg) maximum.
- (D) Tandem axles 37,500 lbs. (17,000 kg) maximum.
- *Width of tire is determined by tire side0wall nomenclature

Axle Restrictions and Remarks